



SPECIFICATION

MATERIAL
 Insulator: PBT & GLASS FILL REINFORCED UL-94V-0
 Contacts: Brass
 Shell: Steel
 Rivet, Boardlock: Copper alloy
CONTACT PLATING
 Gold flash
ELECTRICAL
 Operation voltage: 250 VAC max.
 Current rating: 3 Amps max.
 Contact resistance: 15 mohms max.
 Insulation resistance: 3000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 1000 VAC / minute
 Operating temperature: -55°C TO +105°C
 Part no.

207 A E 09 M G P B G A 1
 1 2 3 4 5 6 7 8 9 10 11

- 1. SERIES NO.
207 = D-SUB 7.2mm PCB
RIGHT ANGLE MACHINED PIN
(D-SUB, 90度 PCB 板型, 車針)
- 2. TYPE: A = Standard
- 3. ENVIRONMENT PROTECTION
MATERIA
E = ROHS 環保料件
- 4. CONTACT NUMBER:
09 = 09 PIN
- 5. CONTACT TYPE:
M = MALE (公)
- 6. CONTACT AREA PLATING:
G = Gold Flash (全金 G/F)
R = 3U" Gold (全金 3U")
A = 5U" Gold (全金 5U")
C = 15U" Gold (全金 15U")
D = 30U" Gold (全金 30U")
- 7. SHELL PLATING:
P = TIN+DIMPLE (鍍錫壓花)
- 8. BRACKET OPTION:
B = PLASTIC/BRACKET (有塑膠腳架)
- 9. RIVET & BOARDLOCK OPTION
G = REAR RIVET W/BOARDLOCK (卯後殼 Z 片)
H = REAR RIVET W/L-SHAPE (卯後殼 L 片)
- 10. PARTS OPTION
A = NON ACCESSORIES (無附件)
B = LOOSE SCREWS 4.8*11.8mm (附 4.8*11.8mm 螺絲)
C = FIXED SCREWS 4.8*11.8mm (鎖 4.8*11.8mm 螺絲)
D = LOOSE SCREWS 5.8*11.8mm (附 5.8*11.8mm 螺絲)
E = FIXED SCREWS 5.8*11.8mm (鎖 5.8*11.8mm 螺絲)
- 11. INSULATOR COLOR
1 = WHITE (白色)
2 = BLUE (藍色)
3 = BLACK (黑色)

| | |
|--------------------------------------|------|
| UNLESS OTHERWISE SPECIFIED TOLERANCE | |
| ANG. | ±5° |
| 0. | ±0.5 |
| .0 | ±0.3 |
| .00 | ±0.2 |

亮泰 (中国) 有限公司

SCALE: AS SHOWN UNIT: mm

DRAWN AVA 07/07/04

CHECKED WAN 07/07/04

APPROVED CHEN 07/07/04

DRAWN NAME:
D-SUB SOLDER MACHINED (D-SUB 焊線車針)
09PIN, MALE (公), 全金, 光孔, 鍍錫壓花

PRODUCT NO. 202AE09MGPA4A1

FILE NAME: 202AE09MGPA4A1

A ECN-20040707001 (TONY) 07/07/04

REV. DESCRIPTION DATE

1 2 3 4 5 6 7 8 A4 REV. A 9 10