

RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: ±0.10mm

SPECIFICATION
MATERIAL
Insulator: PBT & GLASS FILL REINFORCED UL-94V-0
Contacts: Brass
Shell: Steel
Rivet, Boardlock: Copper alloy
CONTACT PLATING
Gold flash
ELECTRICAL

Operation voltage: 250 VAC max.
Current rating: 3 Amps max.
Contact resistance: 15 mohms max.
Insulation resistance: 3000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1000 VAC / minute
Operating temperature: -55°C TO +105°C
Part no.

207 A E 09 M G P B G A 1
1 2 3 4 5 6 7 8 9 10 11

- SERIES NO.
207 = D-SUB 7.2mm PCB
RIGHT ANGLE MACHINED PIN
(D-SUB, 90度 PCB 板型, 車針)
- TYPE: A = Standard
- ENVIRONMENT PROTECTION
MATERIA
E = ROHS 環保料件
- CONTACT NUMBER:
09 = 09 PIN
- CONTACT TYPE:
M = MALE (公)
- CONTACT AREA PLATING:
G = Gold Flash (全金 G/F)
R = 3U" Gold (全金 3U")
A = 5U" Gold (全金 5U")
C = 15U" Gold (全金 15U")
D = 30U" Gold (全金 30U")
- SHELL PLATING:
P = TIN+DIMPLE (鍍錫壓花)
- BRACKET OPTION:
B = PLASTIC/BRACKET (有塑膠腳架)
- RIVET & BOARDLOCK OPTION
G = REAR RIVET W/BOARDLOCK (卯後殼 Z 片)
H = REAR RIVET W/L-SHAPE (卯後殼 L 片)
- PARTS OPTION
A = NON ACCESSORIES (無附件)
B = LOOSE SCREWS 4.8*11.8mm (附 4.8*11.8mm 螺絲)
C = FIXED SCREWS 4.8*11.8mm (鑽 4.8*11.8mm 螺絲)
D = LOOSE SCREWS 5.8*11.8mm (附 5.8*11.8mm 螺絲)
E = FIXED SCREWS 5.8*11.8mm (鑽 5.8*11.8mm 螺絲)
- INSULATOR COLOR
1 = WHITE (白色)
2 = BLUE (藍色)
3 = BLACK (黑色)

| UNLESS OTHERWISE SPECIFIED TOLERANCE | |
|--------------------------------------|------|
| ANG. | ±5° |
| .0 | ±0.5 |
| .0 | ±0.3 |
| .00 | ±0.2 |

SCALE: AS SHOWN UNIT: mm

亮泰 (中国) 有限公司

DRAWN AVA 07/10/04

DRAWN NAME:
D-SUB PCB RIGHT ANGLE MACHINED (D-SUB, 90度插板)
09 PIN, FEMALE (母), 9.4mm 車針, 全金, 鍍支架, 有檔板, 卯四爪 Z 片


CHECKED WAN 07/10/04

APPROVED CHEN 07/10/04

PRODUCT NO. 208AE09FGTDKA1

ECN-20040710001 (TONY)

DATE



SIZE

A4

REV.

A

FILE NAME: 208AE09FGTDKA1

REV. DESCRIPTION

1 2 3 4 5 6 7 8 9 10