


RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: ±0.10mm



parts no.	DIM. a	DIM. b	inner thread
B,C	4.8	11.8	4#40
D,E	5.8	12.0	4#40

SPECIFICATION

MATERIAL
 Insulator: PBT, rated UL94V-0
 Contacts: Brass
 Shell: Steel
 Rivet, Boardlock: Copper alloy
 CONTACT PLATING
 Contact area: 1u"~30u" gold
 ELECTRICAL
 Operation voltage: 250 VAC max.
 Current rating: 3 Amps max.
 Contact resistance: 15 mohms max.
 Insulation resistance: 3000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 1000 VAC / minute
 Operating temperature: -55°C TO +105°C
 Part no.

106 A E 44 M G P C K A 1
 1 2 3 4 5 6 7 8 9 10 11

- SERIES NO.
106 = D-SUB HDD 8.89*2.54mm P.C.B. RIGHT ANGLE (MACHINED PIN)
(D-SUB高密度 90度PCB 車針)
- TYPE: A = Standard
- ENVIRONMENT PROTECTION
MATERIAL:
E = RoHS環保材料
- CONTACT NUMBER:
44 = 44 PIN
- CONTACT TYPE:
M = MALE(公)
- CONTACT AREA PLATING:
G = GOLD FLASH (全金)
R = 3"u GOLD (全金)
A = 5"u GOLD (全金)
C = 15"u GOLD (全金)
D = 30"u GOLD (全金)
- SHELL PLATING:
P = Tin plated+dimple(鍍錫壓花)
- BRACKET OPTION
C = HARDWARE/BRACKET W/O BOARD
(有鐵支架, 沒有檔板)
- RIVET & BOARDLOCK OPTION
K = REAR RIVET W/4-PRONG BOARDLOCK
(卵後殼, 四爪乙片)
- PARTS OPTION
A = NON ACCESSORIES(無附件)
B = LOOSE SCREWS 4.8*11.8mm (附4.8*11.8mm螺絲)
C = FIXED SCREWS 4.8*11.8mm (鋼4.8*11.8mm螺絲)
D = LOOSE SCREWS 5.8*11.8mm (附5.8*11.8mm螺絲)
E = FIXED SCREWS 5.8*11.8mm (鋼5.8*11.8mm螺絲)
- INSULATOR COLOR
1 = WHITE (白色)
2 = BLUE (藍色)
3 = BLACK (黑色)

UNLESS OTHERWISE SPECIFIED TOLERANCE		亮泰 (中国) 有限公司 Lightany (China) Co., Ltd.	
ANG.	±5°		
0.	±0.5	SCALE: As show UNIT: mm	
.0	±0.3		
.00	±0.2		
DRAWN	AVA	07/07/04	DRAWN NAME:
CHECKED	WAN	07/07/04	D-SUB HDD 8.89*2.54mm P.C.B. RIGHT ANGLE(MACHINED), 鐵殼 沒有螺絲+DR 8.89*2.54mm 90度車針, 44PIN, MALE(公), 全金, 卵後殼 卵四爪乙片
APPROVED	CHEN	07/07/04	PRODUCT NO. 106AE44MGPCA1
REV.			FILE NAME: 106AE44MGPCA1

A	ECN-20040707001(TONY)	07/07/04	APPROVED	CHEN	07/07/04	DATE	SIZE	A4	REV.	A
REV.						DESCRIPTION				